



SmartRayVision®



Extreme 3X Spec Sheet

Controller: Specs & Features

- Available in two sizes 10.1" and 13.3" and includes 2 batteries
- Capacitive touchscreen, Intel® core™ processor
- Microsoft® Windows® operating system
- IP65 Ingress Protection, MIL-STD-810H Certified
- HERO (Hazard of EMR to Ordnance) certified
- Military (STIGS) Cyber Secure
- SRV software installed with AI Image Enhancement



Panel: Specs & Features

- Panels available in two sizes: 10"x 12" & "14 x 17"
- Non-glass, DR imager with 4 mm bottom margin
- 1 meter (3.3 ft) drop tested , P67 Ingress Protection
- Operating temps =- 21° to 122° F
- Weight (lbs.) 10x12= 6.4, 14x17= 10.58
- Includes (2) Li-Ion batteries
- Picatinny or arca rail mounting for handle & bipod



Wireless Controller: Specs & Features

- Long range and short range options, 5GHz Op freq.
- **Long range** = 300 meters (985 ft) line of site, IP67, 1 meter (3.3 ft) drop tested, two ethernet ports, 7 pin cable connection, picatinny clamp for generator attachment, powered by DeWalt® batteries
- **Short range** = 10 meters (32 ft) line of site, IP 67, 1 meter drop tested, instant wireless connection w/ no battery required
- Instant, reliable connection & self healing WiFi

