

Extreme 3x Imager Panels



Reliability Meets HD Resolution



Features and Specs

- Available in 10"x12", 14"x17", or Dual
- Real-Time wireless and battery level SITREP on SRV® Software
- (2) Li-Ion batteries included
- Best in class durability and reliability
- 1 meter drop tested
- Picatinny mounting platform for included handle and bipod
- Panel Sling for hands-free carrying*
- Non-glass construction
- 4mm bottom margin
- Produces image in less than 10 seconds

*Panel Sling is a standard accessory for X1417 Panels only.

Extreme 3x Imager Panel Specs

	SRV X1012® Panel	SRV X1417® Panel
Dimensions (inches)	11.2 x 12.75 x 0.7	15.2 x 17.7 x 0.7
Image Area	2560 x 2048 Pixels	2816 x 2304 Pixels
Weight (lbs)	6.4	10.58
Scintillator	Gadox	Gadox
Pixel Pitch (µm)	120	154
Resolution	4.2 lp/mm	3.3 lp/mm
Energy Range (kVp)	400 Max	400 Max
Battery Operation	11 Hours	11 Hours
Ingress Protection	IP67	IP67
Temperature Range (°F)	-21 to 122	-21 to 122
Storage Temp. Range (°F)	-40 to 140	-40 to 140